

PureDRI Hand Dryer



Designed to provide three levels of infection control, fast hand drying, and exceptional energy efficiency, the PureDRI helps reduce contamination while creating cleaner, fresher, and more sustainable environments.



DRY TIME
20
SECONDS



NOISE OUTPUT
76 dBA



RATED POWER
0.2 kW



ANNUAL OPERATING COST
\$33*
PER YEAR

*Based on 200 uses per day, 365 days per year, using average U.S. commercial electricity rates.

TECHNICAL SPECIFICATIONS

Dimensions	10.6" H x 32.3" W x 3.9" D (270 x 820 x 100 mm)
Weight	20.3 lbs (9.2 kg)
Electrical Supply	110–240 VAC, 50/60 Hz
Current Consumption	1.7 A @ 115 VAC / 0.9 A @ 230 VAC
Power Consumption	0.2 kW (220 W)
Dry Time	20 seconds
Operation	Continuous room sanitizing. Automatic, touch-free hand drying and sanitizing.
Aperture Type	Concentrated jet
Air Velocity	112 mph (50 m/s) (measured 4" below outlet)
Air Outlet Temperature	86°F at 68°F ambient temperature
Noise Level	76 dBA measured at 3 feet from the unit
Cover Options	Brushed stainless steel
Color Options	 
Lamp Options	0mg non ozone bulb



BUILT-IN SANITIZING TECHNOLOGY
Helps reduce bacteria and improve hygiene.



7 YEAR WARRANTY
Built for long-lasting performance and reliability.



COLOR OPTIONS
Brushed stainless steel with white (standard)



LOW CARBON FOOTPRINT
Only 0.25g CO₂ per use.



AIRDRI USA
☎ (888) 367-6958
✉ sales@airdri.com
🌐 airdri.com

Noise level: Tested in accordance with ISO 3744 standard.
Operating cost: Based on 200 uses per day, 365 days per year, using average U.S. commercial electricity rates.
CO₂ per use: Based on U.S. EPA eGRID 2022 average CO₂ emissions from the U.S. electricity grid.